



26 cm Woofer


**Key Features:**

Black Anodized Alu Cone

Coated Fibre Glass Dust Cap

Magnet System w. Alu Ring

Die cast Alu Chassis vented below spider

Low Resonance Freq. 23Hz

**Recommendations (please see Tech Note):**

Operating frequency range: fs-1500 Hz

Cabinet volume - closed box: Vbox=82 ltr, f(-3dB)=39 Hz

Cabinet volume - vented box: Vbox=173 ltr, fb=22 Hz, f(-3dB)=22 Hz

**26W/8534G00**
**T-S Parameters:**

Resonance frequency [fs]	23 Hz
Mechanical Q factor [Qms]	9.12
Electrical Q factor [Qes]	0.42
Total Q factor [Qt]	0.40
Force factor [Bl]	10.1 Tm
Mechanical resistance [Rms]	0.80 kg/s
Moving mass [Mms]	50.5 g
Compliance [Cms]	0.95 mm/N
Effective diaph. diameter [D]	211 mm
Effective piston area [Sd]	350 cm <sup>2</sup>
Equivalent volume [Vas]	150 l
Sensitivity (2,83V/1m)	89 dB

**Mechanical Data:**

Voice coil diameter	38 mm
Voice coil height	18 mm
Voice coil layers	2
Gap height	6 mm
Linear excursion	± 6 mm
Max mech. excursion	± 12 mm
Unit weight	2.9 kg
Cabinet Displacement Volume	0.73 l

**Electrical Data:**

Nominal impedance [Zn]	8 Ω
Minimum impedance [Zmin]	6.4 Ω
Maximum impedance [Zo]	117 Ω
DC resistance [Re]	5.7 Ω
Voice coil inductance [Le]	0.96 mH

**Power Handling:**

100h RMS noise test (IEC 18.4) 80 W

Long-term max power (IEC 18.2) 150 W

X-over: None

